

### Narda SignalShark 3310 – The Lab in Your Hand

- ✓ **Reliable:** No risk to miss-out any signal due to 40 MHz RTBW with high POI and HDR. No additional tablet or USB cable needed, that may cause problems. Rugged design.
- ✓ **Lab:** Powerful signal analysis, 4 x RF inputs, SCPI programmable and connectors for additional monitor, mouse and keyboard.
- ✓ **Field:** 10.4" touch handheld to measure at the site, where the real problems occur. Size (w x h x d) 335 mm x 230 mm x 85 mm, Weight ~ 4.1 kg (with one battery), Power consumption ~ 35 W (hot-swappable batteries for long-term measurements)
- ✓ **Save time and money:** No additional lab analyzer needed. No installation time. Up and running in a few seconds. Shorter measurement campaigns due to faster measurements.
- ✓ **Full automatic direction finding:** Reliable and fast DF.



### High Dynamic Range (HDR) Receiver

In real life, you often have to measure signals with a low power level in an environment with strong signals. One example is the measurement of an interferer in a LTE down link band.

It's the same problem as taking a picture of an object in the shadow while being in bright sunlight. Like the traditional camera cannot take a picture of dark and bright objects at once, a conventional analyzer can only perform either high sensitivity or large-signal immunity measurements using a "Normal Mode" or and "Low Distortion Mode".

The special hardware design of SignalShark allows measuring signals under lab conditions as well as real life measurements like the scenario stated above. This is accomplished by supporting three important receiver parameters at the same time for a HDR measurement:

- The Noise Figure / DANL allows measuring signals with a very low power level
- And at the same time the IP2 value and IP3 value protects your system for overload or rather intermodulation in an environment with strong signals.

### Tektronix RSA507A

- ✗ Poor POI and signal analysis (no HDR). Additional tablet/laptop must be connected via USB cable
- ✓ Many optional measurement functions. Can be operated via PC.
- ✓ Size (w x h x d) 299.1 mm x 67.3 mm x 271.3 mm + Tablet, Weight: 1 kg Tablet + 2.99 kg measurement device ~ 3.99 kg Power consumption ~ 15 W + Tablet
- ✗ No full automatic direction finding



### Key Specification Comparison

		Narda SignalShark 3310		Tektronix RSA507A	
<b>Real-time Bandwidth (RTBW)</b>		✓	40 MHz	✓	40 MHz
<b>POI (100% for signals...)</b>		✓	> 3.125 µs in 40 MHz	✗	100 µs in 40 MHz
<b>Frequency Range</b>		✓	8 kHz to 8 GHz	✗	9 kHz to 7.5 GHz
<b>Scan Speed</b>		✓	up to 50 GHz/s	✗	0.9 GHz/s
<b>HDR</b>	<b>DANL (NF)</b>	2 MHz to 30 MHz 30 MHz to 3 GHz	✓ < -160 dBm/Hz (< 14 dB) ✓ < -159 dBm/Hz (< 15 dB)	✗ ✗	<i>typ.</i> -127 dBm/Hz (47 dB) <i>typ.</i> -139 dBm/Hz (35 dB)
	<b>IP2</b>	2 MHz to 30 MHz 30 MHz to 3 GHz	✓ > 56 dBm ✓ <i>typ.</i> 40 dBm	✗ ✗	? +29 dBm
	<b>IP3</b>	2 MHz to 30 MHz 30 MHz to 3 GHz	✓ > 20 dBm ✓ <i>typ.</i> 12 dBm	✗ ✓	<i>typ.</i> +10 dBm <i>typ.</i> +15 dBm

